

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number  
**WO 2005/047838 A1**

(51) International Patent Classification<sup>7</sup>: **G01K 13/08**

(21) International Application Number:  
PCT/US2003/032692

(22) International Filing Date: 14 October 2003 (14.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **THE TIMKEN COMPANY** [US/US]; 1835 Dueber Avenue S.W., Canton, OH 44706 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ADAM, Christian** [FR/FR]; 11, Rue Schoepflin, F-68000 Colmar (FR).

(74) Agent: **BOOKS, Mark E.**; Polster, Lieder, Woodruff & Lucchesi, L.C., 12412 Powerscourt Drive, Suite 200, ST. Louis, MO 63141-3615 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ROTATION SENSOR WITH TEMPERATURE MEASURING FEATURE



(57) Abstract: A temperature sensing system (100) for use with a variable reluctance sensor such as found in vehicle wheel bearing applications, which utilizes existing sensors (12) such as the antilock braking system or traction control system sensors as a direct current resistive temperature gauge. The temperature sensing system (100) includes electrical components (R4, C1) configured to separate the DC voltage (VDC(t)) representative of sensor temperature from the original magnetically induced AC voltage output signal (VSN1(t)) representative of the rotation such as vehicle wheel speed, thereby permitting the temperature sensing system (100) to be retrofitted and installed in vehicles or other components without significant alteration to an existing wiring harness or electrical components.